

I-SAFE 1 STM

SPEED INFORMATION DISPLAY:
SPEED AND PICTOGRAMS

THE I-SAFE 1 ALTERNATES SPEED DISPLAY WITH PICTOGRAM MESSAGES

- ✔ Coloured speed information (green, yellow or red according to the driver behaviour).
- ✔ Pictograms or short text messages.
- ✔ Compact, mobile and easy to handle.
- ✔ Different power possibilities: solar energy, public lighting, 220 V network or battery.

WHY CHOOSE AN I-SAFE?

USEFUL

- ✔ Compact
- ✔ Light
- ✔ Removable battery
- ✔ Predefined settings speed zones
- ✔ Calendar function (up to 4 periods/day)

COMFORTABLE AND USER-FRIENDLY

- ✔ Comprehensive software for data analysis
- ✔ Full standard kit including the fastening system

ADVANTAGES



- ✔ High visibility: 39 cm figures
- ✔ Colour pictograms
- ✔ 4 power possibilities
- ✔ Settings without PC
- ✔ Easy and quick installation

SETTINGS

Choice of predefined settings (digit encoder)
 Custom configuration with USB stick

- ✔ Minimum and maximum speed display thresholds
- ✔ Colour speed thresholds (green, yellow, red)
- ✔ Blinking flash speed threshold
- ✔ Text or pictograms
- ✔ Time slots

TECHNICAL FEATURES

| | |
|--------------------------|---|
| Displayed speed | From 5 to 199 km/h |
| Measured speed | From 5 to 255 km/h |
| Detection range | car: 120 m truck: 150 to 200 m |
| Mounting system | 2 hooks at panel's rear + 2 specific pole brackets |
| Operating temperatures | From -30°C to +65°C |
| Power | Rechargeable 12V/24 Ah battery or 110-220 V (network or public lighting) or solar powered |
| Autonomy | Depending on power supply |
| Frequency | K-Band: 24.125 GHz |
| Transmitted power | <5 mW |
| Communication interface | USB (options: Bluetooth or 3G) |
| Memory | 540 000 measures |
| Dimensions | figures: 384 x 513 mm (H x L) housing: 775 x 655 x 140 mm (H x L x P) |
| Weight (without battery) | 12.4 kg |
| Software | |
| PC running | Windows 10 or higher, minimum 512 MB RAM |
| Disk space | 50 MB |

OPTIONS

- ✔ 3G modern
- ✔ Bluetooth



STANDARD

Directive 2014/53/EC

