

# I-SAFE 2 STM

SPEED INFORMATION DISPLAY:  
SPEED AND TEXT MESSAGES

## THE I-SAFE 2 COMBINES SPEED DISPLAY WITH PICTOGRAM MESSAGES

- ✔ Coloured speed information (green, yellow or red according to the driver behaviour).
- ✔ 2 lines fully configurable text (9 to 10 characters each) or pictograms.
- ✔ Compact, mobile and easy to handle.
- ✔ Different power possibilities: solar energy, public lighting, 220 V network or battery.

## WHY CHOOSE AN I-SAFE?

### USEFUL

- ✔ Compact
- ✔ Light
- ✔ Removable battery
- ✔ Predefined settings speed zones
- ✔ Calendar function (up to 4 periods/day)

### COMFORTABLE AND USER-FRIENDLY

- ✔ Comprehensive software for data analysis
- ✔ Full standard kit including the fastening system

## ADVANTAGES



- ✔ High visibility: 35 cm figures
- ✔ Text and/or pictograms
- ✔ 4 power possibilities
- ✔ Settings without PC
- ✔ Easy and quick installation

## SETTINGS

Choice of predefined settings (digit encoder)  
 Custom configuration with USB stick

- ✔ Minimum and maximum speed display thresholds
- ✔ Colour speed thresholds (green, yellow, red)
- ✔ Blinking flash speed threshold
- ✔ Text or pictograms
- ✔ Time slots

## TECHNICAL FEATURES

Displayed speed	From 5 to 199 km/h
Measured speed	From 5 to 255 km/h
Detection range	car: 120 m truck: 150 to 200 m
Mounting system	2 hooks at panel's rear + 2 specific pole brackets
Operating temperatures	From -30°C to +65°C
Power	Rechargeable 12V/24 Ah battery or 110-220 V (network or public lighting) or solar powered
Autonomy	Depending on power supply
Frequency	K-Band: 24.125 GHz
Transmitted power	<5 mW
Communication interface	USB (options: Bluetooth or 3G)
Memory	540 000 measures
Dimensions	figures: 345 x 520 mm (H x L) text: 160 x 520mm (H x L) - 832 housing: 775 x 655 x 140 mm (H x L x P)
Weight (without battery)	12.4 kg
Software	
PC running	Windows 10 or higher, minimum 512 MB RAM
Disk space	50 MB

## OPTIONS

- ✔ 3G modern
- ✔ Bluetooth



STANDARD

Directive 2014/53/EC

